



**DETAIL A
SCALE 5 : 1**

- NOTES:
 1. ISO 8362-1:2018 VIAL CONTAINING A NECK FINISH WITH BLOWBACK (EUROPEAN STYLE) - MODEL B
 2. CRITICAL DIMENSIONS SHOWN WITH: ϕ
 3. REFERENCE DIMENSIONS SHOWN WITH: ()
 4. FLANGE MEASURED: FOR PROCESS CONTROL, 3.7 ± 0.2 FROM SEALING SURFACE TO INTERSECTION OF OFFSET 0.5MM IN FROM FLANGE O.D.
 5. EDGES SLIGHTLY ROUNDED
 6. DETAIL A: ILLUSTRATED IDEAL PRESENTATIONS. THE TRANSITION TO BLOWBACK IS NOT SHARP-EDGED BUT SLIGHTLY ROUNDED
 7. BRIMFUL: $\sim 26\text{mL} \pm 1.5\text{mL}$
 8. MASS: $\sim 16.2\text{g}$

0	INITIAL RELEASE	CC25042	8/22/2022	BPD	CRF
REVISION	DESCRIPTION	CHANGE #	DATE	REV BY	APPV'D
CORNING		PART NAME: 20R ISO VIAL EUBB			
LIFE SCIENCE TECHNOLOGIES CPT DIVISION		CORNING® VALOR® VIALS			
THIS DRAWING MUST NOT BE REPRODUCED OR COPIED IN ANY WAY WITHOUT THE EXPRESS WRITTEN CONSENT OF CORNING. THE DRAWING IS TO BE USED ONLY FOR THE PURPOSE FOR WHICH IT IS SUPPLIED AND MUST BE RETURNED ON DEMAND.					
UNLESS SPECIFIED DIMS & TOL. ARE INCHES & INTERPRETED PER ASME Y14.5-2009		TOLERANCES UNOS			
3RD		INSTALLATION FRACTIONS $\pm 1/16"$ DETAIL FRACTIONS $\pm 1/64"$			
		1 PLACE DECIMALS $\pm .015"$ 2 PLACE DECIMALS $\pm .010"$ 3 PLACE DECIMALS $\pm .005"$ 4 PLACE DECIMALS $\pm .0005"$ DEGREES $\pm 30'$			
MATERIAL: ALUMINOSILICATE		DESIGNED BY: BPD	MODELED BY: BPD	DRAWN BY: BPD	APPROVED BY: PURCHASING NUMBER: -
HEAT TREAT:		87890-0157-0			
FINISH:		CREATE DATE: 8/2/2022	SIZE B	SCALE 3:1	SHEET 1 OF 1

ASSEMBLY:
DATE PLOTTED: 3/9/2023