

4

3

2

1

B

B

A

A

DETAIL A
SCALE 6 : 1

NOTES:

1. ISO 8362-1:2018 VIAL CONTAINING A NECK FINISH WITH BLOWBACK (EUROPEAN STYLE) - MODEL B
2. CRITICAL DIMENSIONS SHOWN WITH: \ominus
3. REFERENCE DIMENSIONS SHOWN WITH: ()
4. FLANGE MEASURED: FOR PROCESS CONTROL, 3.7 ± 0.2 FROM SEALING SURFACE TO INTERSECTION OF OFFSET 0.5MM IN FROM FLANGE O.D.
5. EDGES SLIGHTLY ROUNDED
6. DETAIL A: ILLUSTRATED IDEAL PRESENTATIONS. THE TRANSITION TO BLOWBACK IS NOT SHARP-EDGED BUT SLIGHTLY ROUNDED
7. BRIMFUL: $\sim 4\text{mL} \pm 0.5\text{mL}$
8. MASS: $\sim 4.4\text{g}$

REVISION	DESCRIPTION	CHANGE NUMBER	DATE	REV BY	APPV'D
0	INITIAL RELEASE	CC25042	8/22/2022	BPD	CRF

CORNING
LIFE SCIENCE TECHNOLOGIES
CPT DIVISION

PART NAME:
2R ISO VIAL EUBB

CORNING VALOR® VIALS

THIS DRAWING MUST NOT BE REPRODUCED OR COPIED IN ANY WAY WITHOUT THE EXPRESS WRITTEN CONSENT OF CORNING. THE DRAWING IS TO BE USED ONLY FOR THE PURPOSE FOR WHICH IT IS SUPPLIED AND MUST BE RETURNED ON DEMAND. THE DRAWING MUST BE TREATED AS STRICTLY CONFIDENTIAL AND MUST NOT BE DISCLOSED TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN CONSENT OF CORNING.

UNLESS SPECIFIED DIMS & TOL. ARE INCHES & INTERPRETED PER ASME Y14.5-2009

TOLERANCES UNOS

INSTALLATION FRACTIONS
DETAIL FRACTIONS

1 PLACE DECIMALS $\pm 1/16"$
2 PLACE DECIMALS $\pm 1/64"$
3 PLACE DECIMALS $\pm .015"$
4 PLACE DECIMALS $\pm .010"$
DEGREES $\pm .005"$
 $\pm .0005"$
 $\pm 30'$

3RD

MATERIAL: ALUMINOSILICATE

DESIGNED BY: BPD

MODELED BY: BPD

DRAWN BY: BPD

APPROVED BY:

PURCHASING NUMBER: -

HEAT TREAT:

87680-0150-0

CREATE DATE: 9/2/2022

SIZE: B

SCALE: 4:1

SHEET: 1 OF 1

ASSEMBLY:
DATE PLOTTED: 11/23/2022

4

3

2

1